

TORQUE SPECIFICATION

Part tightened	N-m	kgf-cm	ft-lbf	
FRONT AXLE				
Hub nut	103	1,050	76	
Tie rod end lock nut	47	480	35	
Steering knuckle x Shock absorber	132	1,350	97	
Steering knuckle x Brake caliper	88	900	65	
Steering knuckle x Tie rod end	49	500	36	
Axle hub x Drive shaft	216	2,200	159	
Lower suspension arm x Steering knuckle	98	1,000	72	
Steering knuckle x Dust cover	8.3	85	74 in.-lbf	
ABS speed sensor set bolt	8.0	82	71 in.-lbf	
FRONT SUSPENSION				
Suspension support x Body	39	400	29	
Suspension support x Piston rod	33	340	24	
Flexible hose and ABS speed sensor wire harness clamp x Shock absorber	29	300	22	
Lower suspension arm front side set bolt	88	900	65	
Lower suspension arm rear side set bolt	132	1,350	97	
Engine rear mount x Suspension member	80	810	59	
Suspension member set bolt	Front side	70	715	52
	Rear side	116	1,185	86
Stabilizer bar bracket set bolt	19	190	14	
Stabilizer bar link set nut	18	180	13	
REAR AXLE				
Hub nut	103	1,050	76	
Axle hub set bolt	52	526	38	
REAR SUSPENSION				
Shock absorber x Body	25	250	18	
Shock absorber x Rear axle beam	49	500	36	
Seat belt set bolt	41	420	30	
Rear seatback set bolt	37	380	27	
Brake line x Flexible hose	15	155	11	
ABS speed sensor wire harness clamp set bolt	5.4	55	48 in.-lbf	
Parking brake cable clamp set nut	5.4	55	48 in.-lbf	
Axle beam x Body	82	837	60	