

STEERING

SERVICE DATA

SS0MY-10

DRIVE BELT		
*Drive belt tension	New belt	440 - 540 N (45 - 55 kgf)
	Used belt	240 - 340 N (25 - 35 kgf)
POWER STEERING FLUID		
Fluid level rise	Maximum	5 mm (0.20 in.)
Fluid pressure at idle speed with valve closed	Minimum	5,400 kPa (55 kgf/cm ² , 781 psi)
STEERING WHEEL		
Steering wheel freeplay	Maximum	30 mm (1.18 in.)
Steering effort at idle speed	Reference	
	Manual steering	28 N·m (285 kgf·cm, 21 ft·lbf)
	Power steering	6.5 N·m (65 kgf·cm, 58 in.·lbf)
POWER STEERING VANE PUMP		
Vane pump rotating torque		0.27 N·m (2.8 kgf·cm, 2.4 in.·lbf) or less
Vane pump shaft and front housing bushing oil clearance	STD	0.021 - 0.043 mm (0.0008 - 0.0017 in.)
	Maximum	0.07 mm (0.0028 in.)
Vane plate height	Minimum	7.6 mm (0.299 in.)
Vane plate thickness	Minimum	1.405 mm (0.0553 in.)
Vane plate length	Minimum	11.993 mm (0.4722 in.)
Vane plate and vane pump rotor groove clearance	Maximum	0.03 mm (0.0012 in.)
Vane plate length	Pump rotor and cam ring mark	
	0	12.001 - 12.003 mm (0.47248 - 0.47256 in.)
	1	11.999 - 12.001 mm (0.47240 - 0.47248 in.)
	2	11.997 - 11.999 mm (0.47232 - 0.47240 in.)
	3	11.995 - 11.997 mm (0.47224 - 0.47232 in.)
	4	11.993 - 11.995 mm (0.47216 - 0.47224 in.)
Spring free length	Minimum	35.8 mm (1.409 in.)
MANUAL STEERING GEAR		
Steering rack runout	Maximum	0.15 mm (0.0059 in.)
Total preload	Turning	0.6 - 1.5 N·m (6 - 15 kgf·cm, 5.2 - 13.0 in.·lbf)
POWER STEERING GEAR		
Steering rack runout	Maximum	0.1 mm (0.004 in.)
Total preload	Turning	1.2 - 1.4 N·m (12 - 14 kgf·cm, 10.4 - 12.2 in.·lbf)

* For use with belt tension gauge